

Pole Puller



Specifications:

PP-30-HD

PP-60-XHD

<i>Performance:</i>	Pull (lb.) at 2,500 psi 60,000	Pull (lb.) at 2,250 psi 125,000
<i>Maximum Pole Size:</i>	18" Diameter 56" Circumference	26" Diameter 81" Circumference
<i>Cylinder:</i>	Stroke 24" Bore 4" Rod 3"	Stroke 24" Bore 6" Rod 4"
<i>Head:</i>	Cam action head has beveled teeth to provide a better grip. Chain (2) 1/2" Grade 100	Cam action head has beveled teeth to provide a better grip. Chain (2) 3/4" Grade 100
<i>Base Weldment:</i>	Exterior 32" x 32" Interior 20" x 26" Weight 700 lbs.	Exterior 46" x 46" Interior 28" x 28" Weight 1,500 lbs.
<i>Lifting Points:</i>	2 lifting eyes on the head Fork pockets: 2 1/2" x 5 1/2" x 32" long	2 lifting eyes on the head Fork pockets: 3 1/4" x 7 1/4" x 46" long

Common Specifications:

Controls:

- Utilize controls on power source (skid steer, crane or derrick)

Hydraulics:

- Required flow rate 5-15 gpm @ 2,500 psi
- Storage of hoses on the base (2) 25 ft. long

1001 Webster Avenue

Waco, TX 76706

254-757-1177

noahg@diversifiedproduct.com

www.line-wise.com

LineWise
by Diversified Products

INSPIRED BY LINEMEN TESTED BY LINEMEN TRUSTED BY LINEMEN

Photos and diagrams are for promotional purposes only.
Product design and specifications may change without notice or obligation.

©2015 Diversified Products