

# Heavy Duty

# Spreader Bars



Model 1150

Actual Appearance will vary with model and length

**Any long material that has a tendency to bend can be handled easily and more safely with a spreader bar.**


**A safe and convenient attachment** for handling rebar cages.

**A popular attachment** with metal building erectors. They use it to handle long metal building beams as well as sheet metal roofing and siding.

### **Universal Fit - "slip-on-the-forks"**

Designed for use with rough terrain forklifts, either straight mast or extendable reach. It comes equipped with fork pockets that will accept up to 7" wide x 2 3/4" thick forks. A center hole provides a hook point that also allows the spreader bar to be suspended from a crane.

MODEL	WEIGHT	EXTENDS	MAXIMUM TOTAL LOAD CAPACITIES			OPTIONAL CENTER HOOK MAX LOAD CAPACITY (using Center Hook ONLY) Add suffix "CH" to model
1150	350 lbs.	8 FT. to 12 FT.	8 FT. SPREAD 8,000 lbs.	10 FT. SPREAD 6,400 lbs.	12 FT. SPREAD 5,000 lbs.	6,000 lbs.
1160	1,100 lbs.	12 FT. to 20 FT.	12 FT. SPREAD 16,000 lbs.	16 FT. SPREAD 11,000 lbs.	20 FT. SPREAD 8,000 lbs.	8,000 lbs.
1190	2,020 lbs.	22 FT. to 38 FT.	22 FT. SPREAD 9,000 lbs.	30 FT. SPREAD 9,000 lbs.	38 FT. SPREAD 9,000 lbs.	9,000 lbs.
1195	2,280 lbs.	20 FT. to 30 FT.	20 FT. SPREAD 23,000 lbs.	25 FT. SPREAD 18,000 lbs.	30 FT. SPREAD 15,000 lbs.	10,000 lbs.



4101 Garland Dr., Fort Worth, TX 76117  
Ph 817-485-6073 Fax 817-428-6008  
USA & Canada Toll Free 800-541-1797  
[www.starindustries.com](http://www.starindustries.com)